

# SCREEN BREATHER VENT


## SBN - SERIES



SBN-Series breather vents combines low profile and air flow into a reality suitable for many applications, particularly where space is limited. Special screen filter is formed by stainless steel wire, offers very high mechanical resistance, guaranteeing long life even under high pressure. Nickel plated brass fitting offers additional corrosion resistance.

Supplied with standard male pipe threads, they can be installed, with little protrusion as a flat integral part of the equipment. Unit should be mounted in a protective position from excessive vibration. Use wrench on hex head to tighten unit to the device. stainless steel wire screen can be easily cleaned by reversing the flow of filtered matter.

### Symbol



### HOW TO ORDER

**SBN** –   – **PT**

Screen Breather Vent

Connection (PT)

18=1/8", 28=1/4"







38=3/8", 48=1/2"

68=3/4", 88=1"

### SPECIFICATIONS

ITEM	MODEL	SBN-18	SBN-28	SBN-38	SBN-48	SBN-68	SBN-88
CONNECTION	PT	1/8"	1/4"	3/8"	1/2"	3/4"	1"
OVERALL LENGTH	IN.	11/16"	7/8"	1"	1-3/16"	1-1/2"	1-5/8"
HEX	IN.	1/2"	5/8"	3/4"	1"	1-1/8"	1-1/2"
NOISE LEVEL @ 60 PSI	dB	70	69	85	85	86	88
NOISE LEVEL @ 115 PSI	dB	74	72	88	90	90	92
MATERIAL	BODY	Brass (Nick Plated)					
	ELEMENT	Stainless steel wire screen (10~150um)					
MAX OPERATING PRESSURE		300 psi (9 kgf/cm <sup>2</sup> )					
OPERATING TEMPERATURE		30~300°F (5~60°C)					
WEIGHT	OZ.	0.30	0.56	0.90	1.45	2.70	--

### FLOW CHARACTERISTICS



\*All tests are performed by Consolidated Laboratories, Inc.